

Φ5MM / 8×8 / 2.1 INCH (53.3MM) SUPER RED / PURE GREEN DOT MATRIX

A-2088DSRYG

Features

- 2.1 inch (53.3mm) matrix height
- Super Red / Pure Green emitting color
- White segment color, black face
- Low current operation
- Easy mounting on PCB boards or sockets
- Lead free, RoHS compliant

Applications

- Digital clocks
- Electronic meters
- Other electronic devices for displaying numerical information

Ordering Information

Part Number	Emission Color	Face Color	Bin Code	Luminous Intensity IV (μcd) (IF=10mA)		
				Min.	Typ.	Max.
A-2088DSRYG	Super Red Pure Green	Black	S	17550	21937	26325
			T	26326	32907	39489
			U	39490	49362	59235

'OPLIGT'

Maximum Ratings

Parameter	Symbol	Value	Unit
Operating temperature	T _{OP}	-35 ~ 85	°C
Storage temperature	T _{STG}	-35 ~ 85	°C
Forward current (T _A =25 °C)	I _F	30	mA per seg
Peak forward current (T _A =25 °C) *1	I _{PF}	120	mA per seg
Reverse voltage (T _A =25 °C)	V _R	5	V per seg
Power consumption (T _A =25 °C)	P	80	mW per seg

*1 at 1/10 Duty Cycle


Electrical / Optical Characteristics (1)(T_A = 25 °C)

Parameter	Symbol	Value	Unit	
Wavelength at peak emission IF = 20mA (Typ.)	λ_P	SR	628	nm
		PG	570	
Dominant wavelength IF = 20mA (Typ.)	λ_D	-	nm	
Spectral bandwidth at 50% IF = 20mA (Typ.)	$\Delta\lambda$	SR	20	nm
		PG	20	
Viewing angle at 50% IF = 20mA (Typ.)	$2\theta_{1/2}$	-	degree	
Forward voltage IF = 20mA	(Min.)	SR	1.80	V
		PG	2.80	
	(Typ.)	SR	2.10	V
		PG	3.20	
	(Max.)	SR	2.40	V
		PG	3.50	
Reverse current V _R = 5V (Max.)	I _R	20	μA	
Optical efficiency IF = 20mA (Typ.)	η_{OPT}	-	lm/W	


Luminous Intensity Bin Groups(T_A = 25 °C & I_F = 10 mA)

Bin Code	Luminous Intensity I _v (μcd)		
	Min.	Typ.	Max.
S	17550	21937	26325
T	26326	32907	39489
U	39490	49362	59235


Electrical/Optical Charateristic (2)




FORWARD CURRENT VS FORWARD VOLTAGE




RELATIVE INTENSITY VS FORWARD CURRENT





FORWARD CURRENT VS DERATING CURVE



LUMINOUS INTENSITY VS AMBIENT TEMPERATURE



Package Outline Dimensions



Notes:

1. All dimensions are in millimeters. Tolerance is ± 0.25 unless otherwise noted.
2. The specifications, characteristics and technical data described in the datasheet are subject to change without prior notice.

Display Soldering Conditions

The recommended conditions for soldering are as follows. Because the component is made with epoxy resin, the units are susceptible to heat. Therefore, the preheating and soldering temperatures should be kept as low as possible to avoid damage.


1 . Manual Soldering Conditions(with 1.5mm Iron tip)

Iron Tip Temperature: 350°C Max, Time: 3s Max

Position: The iron should be situated at least 2mm away from the root of the leads.

2 . Through the Wave Soldering Conditions

Wave Soldering Profile For Lead-free Through-hole LED



3 . Soldering General Notes:

- Toplight recommend manual soldering to be used only for repair and rework purposes. The soldering iron should not exceed 30W in power. The tip of the soldering iron should not touch the reflector case to avoid heat-damage.
- Maintain the pre-heat and peak temperatures with dip units as low as possible and the times as short as is feasible, since the products are susceptible to heat during flow soldering.
- After soldering, allow at least three minutes for the component to cool to room temperature before further operations.
- If components will undergo multiple soldering processes, or other processes where the components may be subjected to intense heat, please check with Toplight for compatibility.